



# Shell Rimula R5 E 10W-40 (CI-4/228.3)

Shell Rimula R5 E

Shell Rimula R5 E



**ENERGISED PROTECTION**  
Adapting to your engine's changing needs

&

Shell Rimula R5 E

Euro 2, 3, US

2002

Shell Rimula R5 E

Euro 2, 3, US 2002

Shell Rimula R6 LM/LME.

&

Shell Rimula R5 E

■ Cummins: CES 20078, 77, 76, 72, 71

■ Mack: EO-M, EO-M+

■ MAN: 3275

■ MB Approval: 228.3

■ Renault Trucks: RLD-2

■ Volvo: VDS-3, VDS-2

■ API: CI-4, CH-4, CG-4, CF-4, CF.

■ Acea: E7, E5, E3

■ Global DHD-1

Shell Rimula R5 E

Shell

Technical Helpdesk



Shell Rimula R5 E



Properties	Method	Shell Rimula R5 E 10W-40 (CI-4/228.3)
		10W-40
@40°C	ASTM D445	90
@100°C	ASTM D445	13.4
@-25°C *	ASTM D5293	6600
	ASTM D2270	150
KOH/	ASTM D2896	10
%	ASTM D874	1.2
@15°C /	ASTM D4052	0.882
°C	ASTM D92	220
°C	ASTM D97	-39

Shell.

&

Shell Rimula R5 E 10W-40 (CI-4/228.3)

<http://www.epc.shell.com/>

« »